



PRODUCT PROFILE



TIRE KLEEN™

FORMULA 9350

Tire Cleaner



DESCRIPTION

Tire Kleen™ is a biodegradable liquid concentrate formulated for cleaning grease and heavy soil loads from whitewalls and tires. The unique blend of complex phosphates, alkaline builders, and non-ionic surfactants provide the optimal level of alkalinity and wetting properties for maximum penetration of soils.

AT A GLANCE



- > *Rapid removal of soils and grime.*
- > *Works great on whitewall tires as well.*

APPLICATIONS

Automatic Carwashes
Self-Serve Carwashes
Tunnel Carwashes

Truck Washing

SPECIFICATIONS

Physical Form: Liquid

pH (1% dilution): 11.0 - 12.0

Recommended Dilution: 32:1 up to 64:1

DOT Class: Corrosive

Color: Red

Fragrance: None

PRODUCT AVAILABILITY

Available Sizes	Container Type	Weight per Container	QTY per pallet	Ships UPS	Additional Hazard Fee
5 Gallon	Round Pail	50 lbs.	20	Yes	Yes
55 Gallon	Poly Drum	500 lbs.	4	No	N/A



PRODUCT PROFILE



FORMULA 9350

Sample Label

DIRECTIONS:
Whitewall degreasing: Mix 32:1 with water (32 parts water to 1 part product), spray on the wheel and allow to sit for 10-15 minutes, then wash with high pressure. Clean: Mix 16:1 with water, spray on the surface, allow to sit for 10-15 minutes, then wash with high pressure.

DESCRIPTION:
Heavy-duty cleaner and degreaser for tires and engines only. Specially formulated to be effective under the most extreme conditions.

INGREDIENTS:
Potassium Hydroxide, Chelating Agent, 2-Butoxyethanol, Proprietary Surfactants Blend.

HAZARD WARNING:
WARNING!! Corrosive Material!! Contact with skin and eyes may cause severe burns. Inhalation of mist can cause irritation and burns to nose, throat and mucous membranes. Ingestion can cause severe burns to mouth, throat and stomach. When handling, wear safety glasses, rubber gloves, apron and rubber boots.

FIRST AID:
Eyes: Flush with water for 15 minutes and get medical attention. Skin: Flush thoroughly with soap and water. Inhalation: Remove patient to fresh air. If breathing has stopped, give artificial respiration. Get medical attention. Ingestion: Dilute by drinking 2 large glasses of water. Call a physician immediately. Do not induce vomiting.

AUTOSHINE
VEHICLE APPEARANCE PRODUCTS

WHITE KLEEN
WHITEWALLS & ENGINE CLEANER

Corrosive Liquid, n.o.s.
(Potassium Hydroxide) UN1760

FORMULA 9350

NET. CONTENT 5 Gal (19 Liters)
55 Gal (209 Liters)

PERFORM
SERIES

KO
KOHLEBERG, INC.
P.O. Box 1000
Springfield, MO 65803
(417) 466-1000
www.komfg.com

ATTENTION: Refer to our MSDS regarding handling and disposal of this product.

IN CASE OF EMERGENCY: Call Chemtrec day or night for assistance and information concerning spilled material, fire, exposure, and other accidents. 1-800-424-9300

Manufacturer warrants this product to its label description. MANUFACTURER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, WHETHER OF FITNESS OR MERCHANTABILITY OR ANY OTHER MATTER RESPECTING THE PRODUCT; IN NO CASE SHALL MANUFACTURER OR SELLER BE LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT. Manufacturer and Seller's liability shall be limited to return of the purchase price.

The above may be affected by state or local government restrictions or laws. Some states do not allow any limitations upon implied warranties of fitness and merchantability for certain products.

042204

Attention: Refer to our Material Safety Data Sheet regarding hazards, personal protection, and disposal of this product.

RESEARCH

Through R&D and field testing, KO Chemists combine creativity with technology to bring you products with the performance you require. Using our sophisticated KO lab we continually test new products, existing products, and our manufacturing processes for effectiveness and affordability. When a new product meets our requirements, it goes to a select group of end-users for real-world evaluation. Only after testing, evaluating, and re-testing is a KO product ready for distribution.

KEEP IT CLEAN™
KO MANUFACTURING, INC.
2720 E. Division • Springfield, MO 65803

800.777.SOAP
800.777.7627
www.komfg.com